

The universal bell with a centring valve suitable for nearly all house connection valves of competitive brands

For installation information see
KAT 54 11-A/B

Product features

- Absolutely corrosion safe type, meets the expectations of DIN 3547 acc. stability and function safety of valves
- Simple installation
- No special tools are required
- Ridgeless adjustable and self-supporting
- No vertical power on the valve
- Safe adjustment by expansion-stop in end position
- High power transfer (acc. DIN 3547) by stable construction of the key bar
- Only 3 sizes are necessary for pipe coverages of 1,00m ... 2,70m

Materials

- Both telescope-square pipes, connection pins and leaf spring of austenitic stainless steel, of stainless steel
- Tow bushing of galvanized ductile cast iron
- Square protector of galvanized cast iron
- End piece, bell and cover of PE, color blue, joint-welded drag safe

Field of application

- For operating ground installed shut-off-valves and house-connection valves in the street cap

Versions

- For VAG Tapping Bridges A11N, A256K, TERRA®K, and House Connection Valve VAG BETA®HA DN 25 - 50, with centering disk, suitable for 10 makes and 17 models
- For VAG EKN® Butterfly Valves
- For gate valves
- With mechanical gate position indicator
- All versions for three pipe coverage areas from 1,00...2,70m (standard)

On request

- Other pipe coverage areas (up to 5,7 m)
- With mechanical and electric gate position indicator

Advice

- for lower requirements acc. to absolutely corrosion safety, easy adjustment e.g. simple installation our "adjustable installation kit" is applicable. Please ask us! In case of inquiry or order we ask for information of the type of the valve, the nominal size and the pipe coverage. The universal bell with center disk fits almost all of the competition-products of house-connection-valves.




Field of application

Valve type	DN	Connection stem square/shaft	Transferable torque	Required torque in acc. with DIN 3547
Gate Valve	40... 150	14 – 19 mm □	300 Nm	250 Nm
	200... 400	24 – 27 mm □	–	250 Nm
VAG EKN® Butterfly Valve	150...1200	16 – 20 mm Ø	300 Nm	250 Nm
Tapping valves VAG BETA® HA Gate Valve	80... 400 25 - 50	12 mm □	190 Nm	100 Nm

Special versions



VAG KLIK-FIX
The new tool-less
stopping system



Yellow lid
For gas valves



Square protector
Version with PIN



**For SYSTEM
TELEKAP**